
USER MANUAL

Thank you for choosing Better Bathrooms.
Please read this manual before installing your product
and keep for future reference.

better bathrooms



ORIMB600 ORIBB600 ORIBR600
ORIMB800 ORIBB800 ORIBR800

- INFRARED SENSOR CONTROL
- IP44 INGRESS PROTECTION
- SINGLE-PERSON ASSEMBLY

V20260917E

CONGRATULATIONS ON YOUR PURCHASE

Our aim at Better Bathrooms is to bring you extraordinary bathroom products for less.

If you're after a modern, traditional, or totally unique bathroom style, we have the fittings and fixtures to bring your ideas to life so you can fall in love with your space every day.

We hope your new product goes above and beyond your expectations. However, should any problems occur, please:

- Log in to your account and contact our customer services team via your self-service portal – betterbathrooms.com/CustomerAccount/Login

- Contact us via betterbathrooms.com/contact/contact-us


CONTENTS

SAFETY	3
BATHROOM ZONES	4
PARTS SUPPLIED	5
TOOLS REQUIRED	5
INSTALLATION DIMENSIONS	6
INSTALLATION	7
OPERATION	8
CLEANING AND MAINTENANCE	9
TECHNICAL SPECIFICATIONS	9

SAFETY



- This mirror should be installed by a qualified electrician.
- This fitting is only suitable for connection to a 220- 240V~ earthed supply in accordance with current IEE wiring regulations and should be installed in accordance with local Building Regulations.
- This is for domestic, indoor use only.
- The fitting should be connected to a dedicated lighting circuit, which must be protected by a 5-amp fuse (or a 6-amp miniature circuit breaker).
- Before installing the fitting, ensure the mains supply is switched off and that the appropriate fuse is removed (or the appropriate circuit breaker is switched off) before commencing installation. Ensure that measures are taken to prevent the supply from being inadvertently reconnected.
- If there is a “Minimum Distance” Label, please do not allow Flammable Materials to rest within that distance from the unit.
- This product may contain delicate parts – be careful during handling and maintenance to avoid breakage.
- Any modification to the fitting will invalidate the warranty and may render the product unsafe.
- A defective appliance may cause an electric shock. Never switch on a defective or damaged appliance. Disconnect the appliance from the mains before seeking assistance.
- This product is IP44 rated, and no part of the installation is allowed to be within bathroom Zones 0 or 1. Installation is permitted within Zone 2.
- This product must be earthed. Before commencing installation, ensure that there are no pipes or wires located behind the wall that may be damaged during drilling.
- Ensure that the hanging location has been decided upon and marked clearly to avoid unwanted damage to the wall due to incorrect positioning.
- Take care of unpacking, and do not use a sharp blade to open it, as this may damage the mirror and void your warranty.
- Installation must only be carried out by a qualified professional or electrician.
- If the external flexible cable or cord of this luminaire is damaged, it shall be exclusively replaced by the manufacturer, his service agent or a similarly qualified person in order to avoid a hazard.
- To reduce the risk of strangulation the flexible wiring connected to this luminaire shall be effectively fixed to the wall if the wiring is within arm's reach.
- The light source of this luminaire is not replaceable; when the light source reaches its end of life, the whole luminaire shall be replaced.

BATHROOM ZONES




Zone 0:	The interior of the bathtub or shower basin.
Zone 1:	The area around the bathtub or shower basin up to a height of 2.25m above the floor
Zone 2:	The area stretching to 0.6m outside the bath or shower and above the bath or shower if over 2.25m

PARTS SUPPLIED


	
Screws (x2)	Wall Plugs (x2)

PLEASE NOTE: It is the installer's responsibility to ensure that the fittings are suitable for the type of wall. Alternative fittings may be required (not supplied). If unsure, professional advice should be sought.


TOOLS REQUIRED (not supplied)




TAPE MEASURE




SPIRIT LEVEL




ELECTRIC DRILL




SCREWDRIVER



HAMMER




8mm DRILL BIT




PENCIL

INSTALLATION DIMENSIONS


NOTE: All diagrams are for illustrative purposes. All dimensions are in mm.






Model Number	A	B	H
ORIMB600	**340mm**	**220mm**	**1900mm**
ORIBB600	**340mm**	**220mm**	
ORIBR600	**340mm**	**220mm**	
ORIMB800	**460mm**	**245mm**	
ORIBB800	**460mm**	**245mm**	
ORIBR800	**460mm**	**245mm**	

IMPORTANT: Install the sensor 150 mm away from any surface.



INSTALLATION



Step 1

Mark and drill the two mounting holes. Then insert the wall plugs and screws.


Step 2


Connect the mirror to the power by hardwiring. All electrical connections must be carried out by a qualified electrician.

All wiring connections must be securely made in accordance with the wiring diagram. All electrical equipment within a bathroom or shower room must be connected to a residual current device (RCD) as per the Building Regulations.

Wiring Colour Coding (for reference):

L (Live)	Brown
N (Neutral	Blue
Earth	Green and Yellow






Step 3

Secure the mirror by aligning the screw heads with the slots on the back of the mirror. Once aligned, carefully lower the mirror so that it locks into position. Ensure the unit is firmly seated and stable before use.

OPERATION

Your mirror has an infrared sensor on the bottom. To activate the light and demister pad, move your hand across the sensor once from about 5cm away.



To turn it off, move your hand across the sensor again.

Hold your hand in front of the sensor to change the light's colour temperature.

CLEANING AND MAINTENANCE


Never use products containing bleach or abrasive cleaners, as this will harm the product's appearance and lifespan.

Use a clean microfiber cloth to clean the mirror.

TECHNICAL SPECIFICATION

Model	ORIMB600	ORIMB800	ORIBR600	ORIBR800	ORIBB600	ORIBB800
LxHxW(cm)	60x60x3.2	80x80x3.2	60x60x3.2	80x80x3.2	60x60x3.2	80x80x3.2
Net Weight(kg)	3.9	6.3	3.9	6.3	3.9	6.3
Power Cord Length(cm)	100	100	100	100	100	100
Rated Power	25W	40W	24W	40W	24W	40W
Input	220V-240V 50\60Hz	220V-240V 50\60Hz	220V-240V 50\60Hz	220V-240V 50\60Hz	220V-240V 50\60Hz	220V-240V 50\60Hz

This product contains a light source of energy efficiency class E and must only be replaced by the manufacturer, its service agent or a similarly qualified person.



DISPOSAL



Recycling facilities are now available for all customers at which you can deposit your old electrical products. Customers will be able to take any old electrical equipment to participating sites run by their local councils.
Please remember that this equipment will be further handled during the recycling process, so please be considerate when depositing your equipment. Please get in touch with the local council for details of your local household waste recycling centres.
At the time of printing the product contains no substances listed within Annex XIV of the Reach Regulations (EC) 1907/2006. In accordance with Article 59 of the same regulation, the following substances are contained within the product at permitted levels: Cadmium.
As a responsible manufacturer, we monitor the regulations to ensure continued compliance. Further information can be provided upon request.

For more information
- visit betterbathrooms.com
- email Support@Betterbathrooms.com
- call 0330 390 3062
- write to Trident Business Park, Neptune Way, Huddersfield, HD2 1UA

better bathrooms
Part of the BuyItDirect Group